

# High speed and reliability. You can count on.

The high-end, solution capable A3 mono printer will meet all of your demanding office requirements. With a print speed of up to 60 pages per minute for A4 size paper and a fast first print out in 3.8 seconds, it will be ready when you need it. A user-friendly 22.8 cm (9 inch) full-colour and intuitive touch panel makes all the device's features easily accessible. This combined with our long-life components will provide exceptional efficiency and reliability, making this printer the perfect choice to increase overall productivity in workgroups and production offices.

**ECOSYS P4060dn****A3 Laser Monochrome****60/30 ppm for A4/A3****1,200 x 1,200 dpi resolution**

ECOSYS P4060dn

## Specifications

### GENERAL

KYOCERA ECOSYS Laser Monochrome, HyPAS™ solution platform  
**Operation panel:** 22.8 cm (9 inch) full-colour touch panel display, 15–90° swivel mounted  
**Engine speed:** Up to 60/30 pages A4/A3 per minute, Duplex print speed: 60 pages A4 per minute  
**Resolution:** 1,200 × 1,200 dpi, 2 bit depth for print quality of 4,800 dpi equivalent × 1,200 dpi  
**Warm-up time:** Approx. 17 seconds or less  
**Time to first print:** Approx. 3.8 seconds or less  
**CPU:** Freescale QorIQ T1024 (Dual Core) 1.2 GHz  
**Memory:** 4 GB RAM, 8 GB SSD + 320 GB HDD  
**Standard interfaces:** 4 × USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10 BaseT/100 BaseTX/1,000 BaseT, slot for optional print server, slot for optional SD card  
**Integrated accounting:** 1,000 department codes  
**Dimensions (W × D × H):** 602 mm × 665 mm × 790 mm  
**Weight:** 77.2 kg  
**Power source:** AC 220–240 V, 50/60 Hz  
**Power consumption:**  
Printing: 820 W  
Ready Mode: 40 W  
Sleep Mode: 1.0 W  
**Noise (sound pressure level ISO 7779 measurement distance of 1 meter):**  
Printing: 55.8 dB(A)  $L_{pA}$   
Ready Mode: 32.4 dB(A)  $L_{pA}$   
**Safety standards:** TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

### PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.  
**Input capacity:** Multi-purpose tray: 150 sheets, 52–300 g/m<sup>2</sup> (Banner 135–165 g/m<sup>2</sup>), A6R–SRA3 (320 × 450 mm), Tab paper (136 × 256 g/m<sup>2</sup>) Banner max. 320 × 1,220 mm; Universal paper cassette: 2 × 500 sheets, 52–300 g/m<sup>2</sup>, upper cassette A6R up to A4R (320 × 450 mm), lower cassette A6R up to SRA3; Max. input capacity with options: 7,150 sheets A4  
**Duplex:** Duplex as standard supports 64–256 g/m<sup>2</sup>, A6R–SRA3 (320 × 450 mm)  
**Output capacity:** Standard 500 sheets face-down, max. output capacity with options 4,300 sheets

### CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752.  
**TK-6330K Toner Kit:** Microfine toner black for 32,000 pages A4, Capacity of starter toner is 16,000 pages A4  
**WT-8500 Waste Toner Bottle:** 70,000 sheets or more (in accordance with ISO/IEC 19752)  
**Staples:** SH-10 for DF-7120/BF-730, SH-12 for DF-7110

### PRINT FUNCTIONS

**Controller language:** PRESCRIBE IIc  
**Emulations:** PCL6 (PCL-5e/PCL-XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS  
**Operating systems:** All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request  
**Fonts/barcodes:** 93 outline fonts (PCL), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)  
**Print features:** Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality, Duplex print mode, N-Up printing mode, Toner save mode  
**Mobile printing support:** AirPrint, Mopria, Google Cloud Print compliant, NFC, Direct Wi-Fi (optional), MyPanel and KYOCERA Mobile Print app for iOS and Android

### OPTIONS

**PF-7100 Paper feeder:** 2 × 500 sheets, 52–300 g/m<sup>2</sup>; A6R–SRA3 (320 × 450 mm), folio  
**PF-7110 Paper feeder:** 2 × 1,500 sheets, 52–300 g/m<sup>2</sup>; A4, B5, letter  
**PF-7120 Paper feeder:** A4 side Deck: 3,000 sheets, 60–300 g/m<sup>2</sup>; A4, B5 (PF-7100 or PF-7110 required)  
**IS-7100 Job separator:** 100-sheet internal job separator, 52–300 g/m<sup>2</sup>; A5R–SRA3  
**CB-7100W Wooden Cabinet:** desk with storage capacity  
**CB-7110M Metal Cabinet:** desk with storage capacity  
**DF-7110<sup>1</sup> Document Finisher + AK-7100:**  
Main tray: Max. 4,000 sheets A4 (3,000 sheets with attachment BF-730); max. 52–300 g/m<sup>2</sup>; max. A6R–SRA3  
Sub tray: 200 sheets A4; 52–300 g/m<sup>2</sup>; A6R–SRA3  
AK-7100: 100 sheets; 52–300 g/m<sup>2</sup>; A6R–SRA3  
Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5–SRA3

### DF-7120<sup>1</sup> Document Finisher + AK-7100:

Main tray: 1,000 sheets A4, 52–300 g/m<sup>2</sup>, A6R–SRA3, 3 positions stapling up to 50 sheets A4 or 30 sheets SRA3  
AK-7100: 100 sheets; 52–300 g/m<sup>2</sup>, A6R–SRA3  
**PH-7C/PH-7D Punch Unit:** for DF-7120/DF-7110: 2-hole/4-hole/Swedish type, 60–300 g/m<sup>2</sup>, A5R–A3  
**MT-730(B) Mailbox sorter:** for DF-7110, 7 bins × 100 sheets A4, 50 sheets A3/B4, 60–165 g/m<sup>2</sup>  
**BF-730 Booklet and tri-folding unit:** for DF-7110  
Half-folding: 52–256 g/m<sup>2</sup>, A3, B4, A4R  
Booklet: Max. 16 sheets (64 pages, 60–90 g/m<sup>2</sup>)  
Non-staple folding: Max. 5 sheets (60–90 g/m<sup>2</sup>)  
Tri-folding: 60–105 g/m<sup>2</sup>, A4R  
Multi tri-folding: 5 sheets (60–90 g/m<sup>2</sup>), 3 sheets (91–105 g/m<sup>2</sup>)  
**Data Security Kit (E):** Encrypts data stored on SSD/HDD.  
In line with ISO 15408 (common criteria) with security level EAL2.  
**NK-7100(B):** Numeric keypad  
**Card Authentication Kit (B) AC:**  
USB IC Card Reader supports various authentication card keys  
**UG-33:** ThinPrint support  
**UG-34:** Emulation (IBM Proprinter/EPSON LQ-850/Line Printer)  
**Optional interfaces:**  
**IB-35:** Direct Wi-Fi Interface  
**IB-50:** Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)  
**IB-51:** Wireless LAN (802.11b/g/n)

### WARRANTY

**Standard warranty:** 1-year warranty as standard<sup>2</sup>  
**Long-life unit warranty:** Kyocera guarantees the drum and developer for 3 years or 600,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.  
**KYOCERA Life:** Up to 5-year on-site warranty extensions available for product and options.

<sup>1</sup> Bridge unit AK-7100 is required for the use of DF-7110/DF-7120.

<sup>2</sup> Depending on the country.

ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. Kyocera's long-life components cost you and the environment less.



**KYOCERA Document Solutions Partner**

FEBRUARY2020DSECOSSYP4060DN/VER1.0

KYOCERA Document Solutions Europe B.V.  
Bloemlaan 4, 2132 NP Hoofddorp, The Netherlands  
Tel +31 (0) 20-654-0000 – Fax +31 (0) 20-653-1256



[kyoceradocumentsolutions.eu](http://kyoceradocumentsolutions.eu)

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.